

TB516^{L3 E3}

Versatile radial tire for loaders, dozers and other equipment



TREAD DESIGN

Wide aggressive for excellent handling, outstanding traction and lateral adhesion

STRUCTURE AND COMPOUND

Tough casing construction with robust shoulder and enhanced sidewall

FEATURES AND BENEFITS

- Excellent traction
- Productivity, stability and comfort
- Resistance to wear and cutting



TIRE SIZE	STAR RATING	LI/SS	RIM WIDTH AND FLANGE	OW [MM]	OW [INCH]	OD [MM]	OD [INCH]	TREAD DEPTH [MM]	TREAD DEPTH [32NDS]	TT/TL
17.5R25 L3	★★	182A	14.00/1.5	445	17.5	1348	53.1	27.0	34.0	TL
17.5R25 E3	★★	167B	14.00/1.5	445	17.5	1348	53.1	27.0	34.0	TL
20.5R25 L3	★★	193A2	17.00/2.0	521	20.5	1493	58.8	30.0	37.8	TL
20.5R25 E3	★★	177B	17.00/2.0	521	20.5	1493	58.8	30.0	37.8	TL
23.5R25 L3	★★	201A2	19.50/2.5	597	23.5	1617	63.7	32.0	40.3	TL
23.5R25 E3	★★	185B	19.50/2.5	597	23.5	1617	63.7	32.0	40.3	TL
26.5R25 L3	★★	209A2	22.00/3.0	673	26.5	1750	68.9	35.0	44.1	TL
26.5R25 E3	★★	193B	22.00/3.0	673	26.5	1750	68.9	35.0	44.1	TL
29.5R25 L3	★★	216A2	25.00/3.5	749	29.5	1874	73.8	38.0	47.9	TL
29.5R25 E3	★★	200B	25.00/3.5	749	29.5	1874	73.8	38.0	47.9	TL
29.5R29 L3	★★	218A2	25.00/3.5	749	29.5	1975	77.8	38.0	47.9	TL
29.5R29 E3	★★	202B	25.00/3.5	749	29.5	1975	77.8	38.0	47.9	TL